## **CLAIMS**

What is claimed is:

1	1.	A communications board comprising:
2		an FR-4 circuit board having a thickness of $0.06 \pm 10\%$ inches;
3		a side-fed patch antenna having the circuit board as a dielectric spacer, the antenna further
4		having:
5		a ground plane on a first side of the circuit board, wherein the ground plane has a
6		width of at least 1.875 $\pm 10\%$ inches and a length of at least 2.25 $\pm 10\%$
7		inches;
8		a rectangular patch on a second side of the circuit board opposite the first side
		wherein the patch has a width of 1.5 $\pm 10\%$ inches and a length of 1.164
Ó		±10% inches; and
		a feed connected to a side of the patch halfway along the width, wherein the feed
		has a width of $0.07 \pm 10\%$ inches and a length of at least $0.625 \pm 10\%$ inches.
	2.	The board of claim 1, wherein the patch antenna is configured to operate between 2.400
2	and	2.483 GHz.
1	3.	The board of claim 1, wherein the patch and feed comprise copper cladding having a
2	thic	kness of approximately 0.063 inches.

45789.02/1981.00900 - 14 -

1	4.	The communications board of claim 1, further comprising:
2		a radio-frequency ("RF") module coupled to the patch antenna and configured to convert
3		signals between baseband and an operating frequency range of the patch antenna.
1	5.	The communications board of claim 4, further comprising:
2		a USB bus interface that couples the RF module to a USB bus.
		A to the analysis of the second s
1	6.	A set-top box comprising:
2		a metallic enclosure having a front face;
3		a non-metallic bezel attached to the front face of the enclosure and defining an interstitial
4		space between the front face and the bezel; and
3 11 14 15 16		a communications board located in said interstitial space, wherein the communications
6		board includes:
7		an FR-4 circuit board having a thickness of $0.06 \pm 10\%$ inches; and
7 48 4 14		a side-fed patch antenna having the circuit board as a dielectric spacer.
1	7.	The set-top box of claim 6, wherein the patch antenna further includes:
2		a ground plane on a first side of the circuit board, wherein the ground plane has a width of
3		at least 1.875 $\pm 10\%$ inches and a length of at least 2.25 $\pm 10\%$ inches;
4		a rectangular patch on a second side of the circuit board opposite the first side, wherein the
5		patch has a width of 1.5 $\pm 10\%$ inches and a length of 1.164 $\pm 10\%$ inches; and
6		a feed connected to a side of the patch halfway along the width, wherein the feed has a
7		width of 0.07 $\pm$ 10% inches and a length of at least 0.625 $\pm$ 10% inches.

45789.02/1981.00900 - 15 -

- 1 8. The set-top box of claim 6, wherein the patch antenna is configured to operate between
- 2 2.400 and 2.483 GHz.
- 1 9. The set-top box of claim 7, wherein the patch and feed comprise copper cladding having a
- 2 thickness of approximately 0.063 inches.
- 1 10. The set-top box of claim 6, further comprising:
- a radio-frequency ("RF") module coupled to the patch antenna and configured to convert signals between baseband and an operating frequency range of the patch antenna.
  - 11. The set-top box of claim 10, further comprising:
    - a USB bus interface coupled to the RF module; and
    - a USB bus that couples the USB bus interface to electronic circuitry in said metallic enclosure.
- 1 12. The set-top box of claim 6, wherein the communications board is mounted flush against the
- 2 front face of the metallic enclosure.
- 1 13. The set-top box of claim 6, wherein the communications board is mounted about 1.23
- 2 inches from the front face of the metallic enclosure.

45789.02/1981.00900 - 16 -

1 14. The set-top box of claim 6, wherein the patch antenna is less than about 0.5 inches from the

2 bezel.

45789.02/1981.00900 - 17 -